

EXTENDS APPROX. 20' WITH 10 ADJOINING SECTIONS FOR A TOTAL OF 200'

5 PROPOSED POWER PEDESTALS SET 18" FROM EDGE, SPACED 40' ON CENTER, (1 EVERY OTHER DOCK SECTION, EXCLUDING THE FIRST SECTION ADJACENT TO THE ACCESS RAMP). EXACT LOCATION TO BE DETERMINED BY TOWN REPRESENTATIVE.

PROPOSED 2" X 8" TREATED DECKING ATTACH WITH 3 1/2" SS BUGLE HEAD SQUARE DRIVE, #8 X 2-5/8", 2 SCREWS PER STRINGER EVERY DECK BOARD (TYP.)

EXISTING ANGLE IRON

PROPOSED 1-1/2" ANGLE IRON 3/16" THICK (TYP.) TO BE WELDED IN PLACE

EXISTING 1/2" GALVANIZED ROD


PROPOSED 2" X 4" STRINGER FASTENED WITH 5/16" CARRIAGE BOLTS SPACED 2' ON CENTER

EXISTING SUPPORT TRUSS


PROPOSED 2" X 8" TREATED DECKING (TYP.)

PROPOSED 2" X 4" STRINGER

PROPOSED 1 1/2" HORNED CLEAT SPACED 3 PER 20' DOCK SECTION 30 TOTAL CLEATS



TOP VIEW



SIDE VIEW

PROPOSED TREATED DECKING
EXISTING SUPPORT TRUSS
PROPOSED 2" X 4" STRINGER

PROPOSED 1-1/2" ANGLE IRON 3/16" THICK (TYP.) TO BE WELDED IN PLACE

BAND BOARD REMOVED FOR FRONT AND SIDE VIEWS

PROPOSED 1 1/2" HORNED CLEAT SPACED 3 PER 20' DOCK SECTION 30 TOTAL CLEATS

PROPOSED ELECTRICAL CONDUIT STRAPPED TO FRAME

2" GAP

FRONT VIEW



KCI TECHNOLOGIES, INC.

ENGINEERS - PLANNERS - SURVEYORS
1352 MARROWS ROAD - SUITE 100 - NEWARK, DELAWARE 19711
PHONE: (302) 731-9176 FAX: (302) 731-7807 Website: www.kci.com

CHESAPEAKE CITY DOCK

DATE: 11/24/14	SCALE: NTS
Drafting: JMS	Check: BCM
KCI JOB# N/A	I